

l'eaunip mat

Primer and mat lacquer top-coat



AFNOR STANDARD T 36.005 - Family I - Class 7b2



L'EAUNIP MAT has 2 main functions :

- Recommended primer for L'EAUNIP BRILLANT and L'EAUNIP SATIN top coats.
- Mat with good flow lacquer paint when used as a top-coat.

Main qualities:

- Easy to coat.
- Low odour.
- Excellent whiteness and hiding power.
- Fast drying
- · Good adhesion on old alkyd surfaces.
- · Suitable on alkaline surfaces.
- Complies with NF environmental rules (certificate N° 27/16)

Technical characteristic data

Composition in white:

Binder : modified acrylic dispersion Solid constituent : Titanium dioxide + mineral

extenders

Mass density at 20° C : 1,48 gr/cm³ +/- 0,05

Non volatile matter in weight : 64% +/- 2% Non volatile matter in volume : 42% +/- 2% Aspect in drum : consistent

Drying (20°C - 65% relative humidity):

• Dry to the touch : 2 hours

• Re-coat : 12 hours

Average spreading rate : 13m²/L
Aspect : lacquer mat
Gloss : < 4% @ 85°

Destination: L'EAUNIP MAT is used as a primer for L'EAUNIP BRILLANT and L'EAUNIP SATIN top coats or any other water-based top coats. As a finishing paint it is a high quality mat lacquer top coat on every usual surfaces of buildings.

Surface preparation: Surfaces must be clean, dry and prepared in conformity with the general conditions of use pursuant to the technical regulations of use (DTU) and standardization currently in force. Clean the surfaces by the appropriated mechanical or chemical means in order to obtain a dry, sound and clean surface. Remove all micro-organism by using **ONIP MOUSSE** or **FONGIVORE**.

Precautions of use: Do not apply on moisture, greasy or frozen surfaces. Old paints have to be sand papered.

	Exterior	Interior
Ambient air temperature	> + 5°C	> 8°C
Temperature of surface ready to paint	> + 5°c < + 35°c	
Humidity of surface ready to paint	< 5%	< 5%
Relative hygrometry	< 80%	< 65%

Use:

Apply L'EAUNIP MAT in 1 coat when used as a primer, in 2 coats as finishing paint:

• Brush (silkor aqua) : dilution 2% water.

Roller (short pile sleeve 10 mm) : pure

• Airless gun (nozzle 17 to 21/1000") : dilution 3 to 5% water.

Tools cleaning : water

Pack size: 4L - 15L

Colours : White allowing + 1200 tints.

Mise à la tembre sans C.O.V.*

Storage in hermetical original pack: 24 months keep away from heat and gel.

Hygiene & safety (directive 2008/58/ CE - 30th adaptation): refer to security data sheet in use.

Maximum content of VOC in the product ready to use (directive 2004/42/CE): 75g/L.

Version: 08/2009

Note: This notice aims informing our customers on the properties of our product. Information data as shown are based on our current knowledge and the tests results from the conditions of use complying with standards and the technical regulations of use (DTU) in force. Due to permanent technical evolution, our customers - before any implementation - have to check with our departments that this notice has not been replaced by an updated version.

This data sheet cancels and replaces all previous versions. In case of complaint, only this document shall be evidence.