

**PRODUCT**

ONA305/022009

**EPOXYSOL AL** is a solvent free, bi-component epoxy, self-levelling, paint for floors.

**USE**

Formulated for interior floors requiring high thickness linings.  
To apply on **PRIMAIRE AEI** primer.

**CHARACTERISTICS**

At 20°C &amp; 65% relative humidity

<b>CLASS</b>	: ONU 1263 - AFNOR T 36005 - Family I, class 6
<b>CUSTOM CODE</b>	: N°3209 90 19
<b>HYGIENE &amp; SECURITY</b>	: EEC maximum content of VOC of the product (cat. A/j): 140g/L (2010). : Maximum content of VOC in the product ready to use: 40g/L.
<b>ASPECT</b>	: gloss
<b>COLOURS</b>	: refer to our SOL colour card
<b>VISCOSITY</b>	: ISO cut N°6 : 200 +/-10 s
<b>MASS DENSITY</b>	: 1.48 +/- 0.02 g/cm <sup>3</sup>
<b>DRY EXTRACT</b>	: 99 +/- 1% in weight and volume

**PERFORMANCES**

- ▶ High chemical resistance.
- ▶ Remarkable film hardness.
- ▶ Applicable in 2 to 3mm thickness.
- ▶ Good mechanical resistance.

**INSTRUCTIONS OF USE**

<b>COATING</b>	: on <b>PRIMAIRE AEI</b> in 1 coat. : apply by roller, spatula, square notched spatula
<b>PREPARATION</b>	: mix the 2 components (base: 100 – hardener DU707: 45) : do not dilute : tools cleaning <b>DILNET DILUENT</b>
<b>SPECIAL APPLICATION</b>	: to obtain 2 to 3 mm thickness (maxi. slope 2%) use a mixer at low speed and slowly pour the NEO3 silica into the mix. When the product is applied remove bubbles with an anti-bubble roller.
<b>DRYING</b>	: pot life : 25min at 20°C / 15min at 25°C. (pot life may considerably vary when temperature is > 20°C) : touch dry : 4 h. : service : walkable 24h - drivable 72h.
<b>THEORETICAL COVERAGE</b>	: at 500 micrometers dry : <b>2 m<sup>2</sup>/ L</b> : at 2 – 3 mm dry : <b>1,3 m<sup>2</sup>/ L + 1 kg NEO3 silica</b>

**PACK SIZE** : pre dosed 4L (3,1kg silica) - 15 L (11,7kg silica)

**STORAGE** : 24 months in original drum. Keep away from frost & heat.

This notice aims informing our customers on the properties of our product. Information data as shown are based on our current knowledge and the tests results from the conditions of use complying with standards and the technical regulations of use in force. Due to permanent technical developments, our customers - prior to any implementation - have to check with our departments that this notice has not been replaced by an updated version.

This data sheet cancels and replaces all previous versions. In case of complaint, this document shall be the only document applicable.