

PRODUCT

PRB1500-12/2006

PRIMAIRE FIXEPOX is bi -component anticorrosion epoxy resin based primer.**USE**

Impregnating and blocking primer for porous and friable surface (cement filler, concrete...)
Colourless primer for transparent dust-free system in interior on every substrates

CHARACTERISTICS

At 20°C & 65% relative humidity

CLASS	: ONU 1263 - AFNOR T 36005 - Family I, class 6b
CUSTOM CODE	: N° 3208 90 19
ASPECT	: Gloss
COLOURS	: Colourless
VISCOSITY	: of the mix : AFNOR cut N°4 : 60 +/-5 s
MASS DENSITY	: of the mix : 1.0 +/- 0.02 g/cm ³
DRY EXTRACT	: of the mix : 33.6 +/- 1 % in weight : of the mix : 30.0 +/- 1 % in volume

PERFORMANCES

- ▶ Excellent adhesion.
- ▶ Good penetration.
- ▶ Corrosion resistance.
- ▶ Compulsory on friable surfaces.
- ▶ Over-coating by any kind of paints.
- ▶ Ideal for dust-free floors

INSTRUCTIONS OF USE

COATING	: in accordance with DTU in force, by brush, roller or gun (nozzle 0.013 to 0.017) : in 1 or 2 coats.
PREPARATION	: mix the 2 pre-dosed components. : base 100 parts – hardener 43,5 parts (DU705) : Do not dilute : Tools cleaning DILUANT PM : let the mix develops for 15 min. before using
POT LIFE of the mix	: 6h to 8 h
DRYING	: out of dust : 15 min. : touch dry : around 2 h. : re-coat : after 6h (beyond 48h a sand papering of the film is needed)
THEORICAL COVERAGE	: at 20 micrometers dry : 15 m²/ L

PACK SIZE (pre-dosed packs) : 1 L - 4 L – 15 L**STORAGE** : 24 months in original drum. Keep away from frost & heat.

This notice aims informing our customers on the properties of our product. Information data as shown are based on our current knowledge and the tests results from the conditions of use complying with standards and the technical regulations of use in force. Due to permanent technical developments, our customers - prior to any implementation - have to check with our departments that this notice has not been replaced by an updated version.

This data sheet cancels and replaces all previous versions. In case of complaint, this document shall be the only document applicable.