



**AFNOR STANDARD** T 36.005 - Family II – Class 2b  
XP P 84403 D3  
EN 1062-1 E5 S2 V2 W2 A0

**INSTADUR** is a waterbased textured paint allowing various finishing depending on the kind of roller used for its application.

### Main qualities :

- Allowing various finishing aspects.
- Masking of small cracks.
- Easy to coat.



- NF Environnement certificate.
- Recommended finishing for ETICS systems.
- Good water vapour permeability

### Technical characteristic data

<p>Composition in white :</p> <p>Binder : acrylic resin</p> <p>Solid constituent : Titanium dioxide + fillers.</p> <p>Mass density at 20°C : 1,60 gr/cm<sup>3</sup> +/- 0,05</p> <p>Non volatile matter in weight : 75% +/- 2%</p> <p>Non volatile matter in volume : 61% +/- 2%</p>	<p>Drying (20°C – 65% relative humidity) :</p> <ul style="list-style-type: none"> <li>• Dry to the touch : 24 hours</li> <li>• Re-coat : 2 days</li> </ul> <p>Average spreading rate : 1 m<sup>2</sup>/L</p> <p>Aspect in drum : thick</p> <p>Aspect when dry : mat</p>
--	---

### Destination :

**INSTADUR** is a textured paint used for exterior decoration.

### Surface preparation :

Surfaces must be clean, dry and prepared in conformity with the general conditions of use pursuant to the technical regulations of use (DTU) and standardization currently in force. Clean the surfaces by the appropriated mechanical or chemical means in order to obtain a dry, sound and clean surface. Remove any micro-organisms and algae with **ONIP MOUSSE** or **FONGIVORE**. For specific or doubtful surfaces, refer to our book of Facade to use the proper primers and their consumption.

**Precautions of use :** Do not apply on moisture, greasy or frozen surfaces.

	Exterior
Ambient air temperature	> 5°C
Surface temperature	minimum + 5°C / maximum + 35°C
Humidity of surface ready to paint	< 5%
Relative hygrometry	< 80%

### Use :

**INSTADUR** has to be coated with a roller.

The choice of the roller will depend on the surface condition and type and of the expected final aspect.

Tools cleaning : water.

**Pack size :** White : 15 L

### Colours :

- White
- 120 colours are available in the Façade Color'Onip colour card .



**Storage in hermetical original pack :** 24 months keep away from heat and gel.

### Hygiene and security (directive 2008/58/CE – 30<sup>th</sup> adaptation) :

Refer to security data sheet in force on : <http://www.onip.com>

Maximum content of VOC in the product ready to use (directive 2004/42/CE) : 10g/l

**Version : 02/2010**

**Note :** This notice aims informing our customers on the properties of our product. Information data as shown are based on our current knowledge and the tests results from the conditions of use complying with standards and the technical regulations of use (DTU) in force. Due to permanent technical evolution, our customers - before any implementation - have to check with our departments that this notice has not been replaced by an updated version. This data sheet cancels and replaces all previous versions. In case of complaint, only this document shall be evidence.

## PEINTURES ONIP

Export Department : LES PEINTURES SAFE – 38 rue Richard Vian – 91530 SAINT CHERON - FRANCE

Tel : 33 (0) 1 69 14 15 30 – Fax : 33 (0) 1 69 14 15 35 + 33 (0) 64 56 57 61 - Email [salle@onip.com](mailto:salle@onip.com)

Commercial & administrative departments : 125-127, avenue de Fontainebleau - 94276 LE KREMLIN-BICETRE Cedex - FRANCE

Tel : 33 (0) 1 46 72 30 95 – Fax : 33 (0) 1 46 72 36 65 - Email [administratif@onip.com](mailto:administratif@onip.com)

Central warehouse and laboratory - Usine du Val de l'Iton - 27400 HONDOUVILLE - FRANCE

Tel : 33 (0) 2 32 50 90 16 – Fax : 33 (0) 2 32 50 90 20 - Email [labo@onip.com](mailto:labo@onip.com)

**Production units are certified ISO 9001/2000**