



AFNOR STANDARD T 36.005 - Family I - Class 7b2

LABEL'ONIP IMPRESSION is the first matt levelling primer labelled with the European Eco-label.

LABEL'ONIP IMPRESSION is the new generation of water-based paint combining levelling finishing, film hardness of alkyd paint to odourless property of acrylic.

Main qualities :

- Easy to coat.
- Very low odour.
- Excellent whiteness and hiding power.
- Good film hardness.



- Fast drying
- Certified European Eco-label Licence N°FR/05/03.
- Good adhesion on old alkyd surfaces.
- Suitable on alkaline surfaces.

Technical characteristic data

Composition in white :	Aspect in drum	: consistent
Binder	Drying (20°C - 65% relative humidity) :	
Solid constituent	• Dry to the touch	: 1 hour
Mass density at 20°C	• Re-coat	: 12 hours
Non volatile matter in weight	Average spreading rate	: 9 to 10m ² /L
Non volatile matter in volume	Aspect	: mat levelling
	Gloss	: < 4% @ 85°

Destination :

LABEL'ONIP IMPRESSION is a matt acrylic primer used on most on most types of internal sound and dry coverings and masonry.

Surface preparation :

Surfaces must be clean, dry and prepared in conformity with the general conditions of use pursuant to the technical regulations of use (DTU) and standardization currently in force. Clean the surfaces by the appropriated mechanical or chemical means in order to obtain a dry, sound and clean surface. Remove all micro-organisms by using **ONIP MOUSSE** or **FONGIVORE**.

Precautions of use : Ensure the substrate is dry, free from grease and other contaminants. Dust off thoroughly. old previously painted substrates will be sandpapered.

	Interior
Ambient air temperature	> 8°C
Humidity of surface ready to paint	< 5%
Relative hygrometry	< 65%

Use :

Apply **LABEL'ONIP IMPRESSION pure without dilution** in 1 coat :

- Brush (silkor aqua).
- Roller (short pile sleeve 5 mm to obtain a levelling finishing).
- Roller (short pile sleeve 10 mm to obtain a fine textured finishing).
- Airless gun (nozzle 15 to 21/1000") maxi dilution 5% water.
- Tools cleaning : water.

Pack size : 1L - 4L - 15L

Colours : White allowing + 1200 tints.



Storage in hermetical original pack : 24 months keep away from heat and gel.

Hygiene & safety (directive 2008/58/ CE - 30th adaptation) : refer to security data sheet in use.

Maximum content of VOC in the product ready to use (directive 2004/42/CE) : 15g/L.

Version : 08/2009

Note : This notice aims informing our customers on the properties of our product. Information data as shown are based on our current knowledge and the tests results from the conditions of use complying with standards and the technical regulations of use (DTU) in force. Due to permanent technical evolution, our customers - before any implementation - have to check with our departments that this notice has not been replaced by an updated version. This data sheet cancels and replaces all previous versions. In case of complaint, only this document shall be evidence.

PEINTURES ONIP

Export Department : LES PEINTURES SAFE - 38 rue Richard Vian - 91530 SAINT CHERON - FRANCE

Tel : 33 (0) 1 69 14 15 30 - Fax : 33 (0) 1 69 14 15 35 + 33 (0) 64 56 57 61 - Email salle@onip.com

Commercial & administrative departments : 125-127, avenue de Fontainebleau - 94276 LE KREMLIN-BICETRE Cedex - FRANCE

Tel : 33 (0) 1 46 72 30 95 - Fax : 33 (0) 1 46 72 36 65 - Email administratif@onip.com

Central warehouse and laboratory - Usine du Val de l'Iton - 27400 HONDOUVILLE - FRANCE

Tel : 33 (0) 2 32 50 90 16 - Fax : 33 (0) 2 32 50 90 20 - Email labo@onip.com

Production units are certified ISO 9001/2000